Weidmüller ⊒E

Conductor markers
SF 0/21 NEUTRAL WS V2

SlimFix is a conductor and cable marker system with a space-saving design. The markers can be fitted even after the wiring has been installed. They are made from halogen-free material and conform to fire protection classification V0/V2. SlimFix is an acknowledged and approved marker type in transport engineering. Attaching even small markers is no problem with the SF tool.

- Halogen-free material
- Fire protection classification V0/V2
- Approved and listed markers for traffic engineering
- Attach to conductor cross-sections above 16.0 mm² with cable ties
- Markers in proven multicard format

General ordering data

Order No.	1918500000
Type	SF 0/21 NEUTRAL WS V2
Version	Conductor markers, MultiCard, 21 x 3.2 mm, Polyamide 66, Colour: White
GTIN (EAN)	4032248553921
Qty.	400 pc(s).

Creation date March 9, 2012 4:51:18 PM CET

Conductor markers
SF 0/21 NEUTRAL WS V2

Technical data

Dimensions

Length	21 mm	Width	3.2 mm
Height	3.2 mm		

Markings

Cadmium	No	Can be labelled with thermal transfer printers	No
Can be printed with plotter	Yes	Can be written with dot-matrix printer	No
Can be written with laser printer	No	Colour	White
Conductor O.D.	1.2 - 1.6mm	Conductor cross-section, max.	0.5 mm²
Conductor cross-section, min.	0.25 mm²	Flammability class UL 94	V-2
Halogen	No	Insulation cross-section, max.	1.6 mm
Material	Polyamide 66	Material colour according to resistance code	9
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Pin can be written (STI)	Yes	PrintJet	Yes
Silicone	No	Size of labelling field	21x3.2 mm
Speed marking laser	Yes	Type of printing	blank

Classifications

ETIM 2.0	EC001530	ETIM 3.0	EC001530
ETIM 4.0	EC001530	UNSPSC	44-12-17-08
eClass 4.1	24-19-02-19	eClass 5.1	27-14-91-03
eClass 6.0	27-14-91-03	eClass 7.0	27149103

Product information

Product description	SlimFix made from V2 material is a conductor and cable marker system with a space-saving design. The SF V2 made from halogen free material exhibits good mechanical and printing characteristics. Arial is the recommended font when using the PrintJet. The SF tool permits easy installation. • halogen free material • flammability rating V2 • SFX attached with cable ties (3.6 mm wide)

Approvals

Approvals

Creation date March 9, 2012 4:51:18 PM CET