



**Type 1**

Male-male  $\varnothing$  4 mm stackable patchcord, retractable sleeve  
 Cordon mâle-mâle  $\varnothing$  4 mm + reprise arrière, fourreau rétractable  
 Messleitung mit  $\varnothing$  4 mm Stecker, stapelbar, retraktierbar



**Type 2**

Male-male  $\varnothing$  4 mm patchcord, retractable sleeve  
 Cordon mâle-mâle  $\varnothing$  4 mm, fourreau rétractable  
 Messleitung mit  $\varnothing$  4 mm Stecker, retraktierbar

Reference - Référence - Bestell-Nr	L cm	Wire Câble Litze	Max current I admissible Bemessungs- strom	Voltage Tension Bemessungs- spannung	m $\Omega$ maxi	Pack	Colours Couleurs Farben #												
							R	N	Bl	V	J	Bc							
							Type 1	Type 2											
2210/600 V - 10 # 2210/600 V - 25 # 2210/600 V - 50 # 2210/600 V - 100 # 2210/600 V - 150 # 2210/600 V - 200 #	2510 - 10 # 2510 - 25 # 2510 - 50 # 2510 - 100 # 2510 - 150 # 2510 - 200 #	10 25 50 100 150 200	PVC 0,75 mm <sup>2</sup> T °C - 20 + 80	600 V - CAT II	12 A	10 12 15 30 45 55	10	Red - Rouge - Rot	Black - Noir - Schwarz	Blue - Bleu - Blau	Green - Vert - Grün	Yellow - Jaune - Gelb	White - Blanc - Weiss						
2211/600 V - 10 # 2211/600 V - 25 # 2211/600 V - 50 # 2211/600 V - 100 # 2211/600 V - 150 # 2211/600 V - 200 #	2511 - 10 # 2511 - 25 # 2511 - 50 # 2511 - 100 # 2511 - 150 # 2511 - 200 #	10 25 50 100 150 200	Silicone 0,75 mm <sup>2</sup> T °C - 60 + 180 (pic + 230)			10 12 15 30 45 55													
2212/600 V - 25 # 2212/600 V - 50 # 2212/600 V - 100 # 2212/600 V - 150 # 2212/600 V - 200 #	2512 - 25 # 2512 - 50 # 2512 - 100 # 2512 - 150 # 2512 - 200 #	25 50 100 150 200	PVC 1,00 mm <sup>2</sup> T °C - 20 + 80			20 A								12 15 25 35 45	10				
2219/600 V - 25 # 2219/600 V - 50 # 2219/600 V - 100 # 2219/600 V - 150 # 2219/600 V - 200 #	2519 - 25 # 2519 - 50 # 2519 - 100 # 2519 - 150 # 2519 - 200 #	25 50 100 150 200	Silicone 1,00 mm <sup>2</sup> T °C - 60 + 180 (pic + 230)											12 15 25 35 45					
2215/600 V - 25 # 2215/600 V - 50 # 2215/600 V - 100 # 2215/600 V - 150 # 2215/600 V - 200 #	2515 - 25 # 2515 - 50 # 2515 - 100 # 2515 - 150 # 2515 - 200 #	25 50 100 150 200	PVC 1,50 mm <sup>2</sup> T °C - 20 + 80											25 A		12 15 20 25 30	10		
2213/600 V - 25 # 2213/600 V - 50 # 2213/600 V - 100 # 2213/600 V - 150 # 2213/600 V - 200 #	2513 - 25 # 2513 - 50 # 2513 - 100 # 2513 - 150 # 2513 - 200 #	25 50 100 150 200	Silicone 1,50 mm <sup>2</sup> T °C - 60 + 180 (pic + 230)													12 15 20 25 30			
2217/600 V - 25 # 2217/600 V - 50 # 2217/600 V - 100 # 2217/600 V - 150 # 2217/600 V - 200 #	2517 - 25 # 2517 - 50 # 2517 - 100 # 2517 - 150 # 2517 - 200 #	25 50 100 150 200	PVC 2,50 mm <sup>2</sup> T °C - 20 + 80													36 A		12 15 20 25 30	10
2214/600 V - 25 # 2214/600 V - 50 # 2214/600 V - 100 # 2214/600 V - 150 # 2214/600 V - 200 #	2514 - 25 # 2514 - 50 # 2514 - 100 # 2514 - 150 # 2514 - 200 #	25 50 100 150 200	Silicone 2,50 mm <sup>2</sup> T °C - 60 + 180 (pic + 230)															12 15 20 25 30	

Material : Contacts : brass and CuBe / Ni (Au/Ni feasible) .Insulators : Polypropylene.  
 Matière : Contacts : laiton et CuBe / Ni (Au/Ni possible) . Isolants : Polypropylène.  
 Material : Kontakte : CuBe und Messing vernickelt/Au/Ni auf Anfrage. Isolation : Polypropylen.