

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 23\_N-50-0-16/133\_N

Rev.: B



### Description

Straight panel receptacle jack, flange mount

Interface standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 11 GHz

#### Mechanical Data

Weight 0.0141 kg

#### Environmental Data

Operating Temperature -65 °C to 165 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

|                |                        |
|----------------|------------------------|
| Centre contact | Copper Beryllium Alloy |
| Outer contact  | Brass                  |
| Body           | Brass                  |
| Insulator      | PFA / PTFE             |

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPLATE (R) Plating  
SUCOPLATE (R) Plating

### Related Documents

|                   |              |
|-------------------|--------------|
| Outline drawing   | DOU-00010111 |
| Catalogue drawing | DCA-00010113 |

### Ordering Information

|                |                     |
|----------------|---------------------|
| Single package | 23_N-50-0-16/133_NE |
|----------------|---------------------|

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
**RF Technology**  
**9100 Herisau, Switzerland**  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
[www.hubersuhner.com](http://www.hubersuhner.com)

**HUBER+SUHNER – Excellence in Connectivity Solutions**