HUBER+SUHNER[®] DATA SHEET Within Series Adapter: 34 SMA-50-0-3/111 N



Description

Bulkhead adaptor jack/jack SMA jack (female) / SMA jack (female)

Interface standards IEC 60169-15 MIL-STD-348A/310 CECC 22110

> **50** Ω 18 GHz

DC to 3 GHz

-20 °C to 165 °C

Copper Beryllium Alloy

Copper Beryllium Alloy

Copper Beryllium Alloy

FPM (Fluor Elastomer)

Copper Beryllium Alloy

Copper Beryllium Alloy

Copper Beryllium Alloy

FPM (Fluor Elastomer)

not compliant

Material

PFA / PTFE

PFA / PTFE

DOU-00013644

DOU-00008860

Material

≥ 26 dB

2 Nm

500 0.0068 kg

Benefits

Hermetic sealed connector Water protection according to IP 68

Technical Data

Electrical Data

Impedance Interface frequency max. Frequency range Return loss

Mechanical Data

Chassis torque Number of matings Weight

Environmental Data

Operating Temperature 2002/95/EC (RoHS)

Material Data

Piece Parts (SMA) Centre contact Outer contact Body Insulator Gasket

Piece Parts (SMA) Centre contact Outer contact Bodv Insulator Gasket

Related Documents

Outline drawing Mounting hole

Ordering Information Single package

34 SMA-50-0-3/111 NE

Additional Information

Remarks

Hermetically sealed: Leakage rate 10-7 Torr l/sec (atm cc/s)

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



3 to 7 GHz ≥ 20 dB

7 to 18 GHz ≥ 17 dB

Surface Plating

Gold Plating (Nickel underplated) Gold Plating (Nickel underplated)

Surface Plating

Gold Plating (Nickel underplated) Gold Plating (Nickel underplated) Gold Plating (Nickel underplated)

Gold Plating (Nickel underplated)



Uncontrolled Copy

HUBER+SUHNER AG **RF** Protection 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 +41 (0)71 353 47 51 Fax www.hubersuhner.com