

Coaxial Cable Connector 11_N-50-7-82/133_N

Description

Straight cable plug

Ingress protection according to IP67



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	11 GHz
Frequency range	DC to 6 GHz
Return loss	≥ 30 dB

Mechanical Data

Centre contact	plugged
Outer contact	clamped
Weight	0.0546 kg

Environmental Data

Operating temperature	-40 °C to 160 °C
2011/65/EU (RoHS)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing	DOU-00101501
Assembly instruction	DOC-0000253737

Ordering Information

Single package	11_N-50-7-82/133_NE
----------------	---------------------

Additional Information

Suitable cables	S_07162_B, SPUMA_400-FR, LMR-400
Interface standards	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Diese Zeichnung ist unser geistiges Eigentum und darf ohne unsere Einwilligung weder kopiert, vervielfältigt noch Dritten oder Konkurrenzfirmen zugänglich gemacht werden. (Art. 12 B.G.)
This drawing is copyright. Information contained thereon is supplied in confidence and must not be used for any other purpose than which it was supplied, or be reproduced without written permission of the owners.

Cable shortening dimension

