

Contre-écrous en laiton nickelé
Gegenmuttern Messing
Lock-nuts nickel-plated brass

Matière : laiton nickelé
Exécution : 6 pans (hexagonal)

Material: Messing vernickelt
Ausführung: 6-kant

Material: Nickel-plated brass
Type: hexagonal design

+200°C
-40°C



Référence
article




G



mm

M
mm

Filetage métrique
Gewinde metrisch
Thread metric


A8000.06.1	M	6x0,75	9	2,8
A8000.06	M	6x1,0	9	2,8
A8000.08.1	M	8x1,0	11	2,8
A8000.08	M	8x1,25	11	2,8
A8000.10.1	M	10x1,0	13	2,8
A8000.10	M	10x1,5	13	2,8
A8000.12	M	12x1,5	15	3,0
A8000.17	M	16x1,5	19	3,0
A8000.20	M	20x1,5	24	3,5
A8000.25	M	25x1,5	30	4,0
A8000.32	M	32x1,5	36	4,5
A8000.40	M	40x1,5	46	4,0
A8000.50	M	50x1,5	55	5,5
A8000.63	M	63x1,5	70	6,0
A8000.75	M	75x1,5	80	6,0
A8000.085	M	85x2,0	95	8,0
A8000.095	M	95x2,0	110	9,0
A8000.100	M	100x3,0	115	9,0
A8000.105	M	105x3,0	120	9,0
A8000.115	M	115x3,0	125	10,0

Filetage Pg
Gewinde Pg
Thread Pg


A8007	Pg	7	15	2,8
A8009	Pg	9	18	2,8
A8011	Pg	11	21	3,0
A8013	Pg	13	23	3,0
A8016	Pg	16	26	3,0
A8021	Pg	21	32	3,5
A8029	Pg	29	41	4,0
A8036	Pg	36	51	5,0
A8042	Pg	42	60	5,0
A8048.48	Pg	48	64	5,5

Filetage au pas gaz
Gasrohr - Gewinde
Thread gas-pipe


A80 ^{3/8}	G	G 3/8"	19	3,0
A80 ^{1/2}	G	G 1/2"	24	3,0
A80 ^{5/8}	G	G 5/8"	26	3,0
A80 ^{3/4}	G	G 3/4"	30	3,5
A801	G	G 1"	38	4,5
A801 ^{1/4}	G	G 1 1/4"	46	5,0
A801 ^{1/2}	G	G 1 1/2"	51	5,0
A8048	G	G 2"	64	5,5

**Contre-écrous
en acier inoxydable**

**Gegenmuttern
aus Stahl, rostfrei**

**Lock-nuts made of stainless
steel, rustproof**

Matière : CrNi acier inoxydable A2
DIN 1.4305 / AISI 303
Exécution : 6 pans (hexagonal)

Material: CrNi Stahl A2
DIN 1.4305 / AISI 303
Ausführung: 6-kant

Material: CrNi Stainless steel A2
DIN 1.4305 / AISI 303
Type: hexagonal design

+300°C
-40°C



Référence
article



G



mm

M
mm

Filetage métrique

Gewinde metrisch

Thread metric



A8008.96	M 8x1,25	11	2,8
A8010.96	M10x1,5	13	2,8
A8012.96	M12x1,5	17	3,0
A8017.96	M16x1,5	19	3,0
A8020.96	M20x1,5	24	3,5
A8025.96	M25x1,5	30	3,5
A8032.96	M32x1,5	36	4,5
A8040.96	M40x1,5	46	4,5
A8050.96	M50x1,5	55	5,5
A8063.96	M63x1,5	70	6,0

Filetage Pg

Gewinde Pg

Thread Pg



A8007.96	Pg 7	17	3,5
A8009.96	Pg 9	19	3,5
A8011.96	Pg 11	22	3,5
A8013.96	Pg 13	24	4,0
A8016.96	Pg 16	27	4,0
A8021.96	Pg 21	32	4,5
A8029.96	Pg 29	41	5,5
A8036.96	Pg 36	51	6,0

Matière : CrNiMo acier inoxydable A4
DIN 1.4435 / AISI 316L
Exécution : 6 pans (hexagonal)

Material: CrNiMo Stahl A4
DIN 1.4435 / AISI 316L
Ausführung: 6-kant

Material: CrNiMo Stainless steel A4
DIN 1.4435 / AISI 316L
Type: hexagonal design

Filetage métrique

Gewinde metrisch

Thread metric



A8008.98	M 8x1,25	11	2,8
A8010.98	M10x1,5	13	3,0
A8012.98	M12x1,5	15	3,0
A8017.98	M16x1,5	19	3,5
A8020.98	M20x1,5	24	3,5
A8025.98	M25x1,5	30	4,5
A8032.98	M32x1,5	36	4,5
A8040.98	M40x1,5	46	4,5
A8050.98	M50x1,5	55	5,5
A8063.98	M63x1,5	70	6,0

Contre-écrous spéciaux**Spezielle Gegenmuttern****Special Lock-nuts**

Matière : laiton nickelé
Exécution : 6 pans, type épais

Material: Messing vernickelt
Ausführung: dick, 6-kant

Material: Nickel-plated brass
Type: thick type, hexagonal design

+200°C
-40°C



Référence
article




G



mm

M

mm

Filetage métrique**Gewinde metrisch****Thread metric**

A8300.12	M12x1,5	15	5,0
A8300.17	M16x1,5	19	5,0
A8300.20	M20x1,5	24	5,5
A8300.25	M25x1,5	30	5,5
A8300.32	M32x1,5	36	6,0
A8300.40	M40x1,5	46	7,0

Filetage Pg**Gewinde Pg****Thread Pg**

A8300.07	Pg 7	15	5,0
A8300.09	Pg 9	18	5,0
A8300.11	Pg 11	21	5,0
A8300.13	Pg 13	23	5,5
A8300.16	Pg 16	26	5,5
A8300.21	Pg 21	32	6,0
A8300.29	Pg 29	41	7,0

Contre-écrous à gorge pour joint torique**Gegenmuttern Messing, mit Hinterstich****Fixing lock nut nickel-plated brass with recess**

Matière : laiton nickelé
Exécution : 6 pans, type épais
Joint torique : à commander séparément

Material: Messing vernickelt
Ausführung: dick, 6-kant
O-Ring: Separat bestellen

Material: Nickel-plated brass
Type: thick type, hexagonal design
O-ring: To be ordered separately

+200°C
-40°C



Référence
article



G



mm

M
mm

Code
joint torique

Filetage métrique**Gewinde metrisch****Thread metric**

A8300.12.1	M12x1,5	15	5,0	A1007.00.08
A8300.17.1	M16x1,5	19	5,0	A1016.00.15.08
A8300.20.1	M20x1,5	24	5,5	A1016.00.08
A8300.25.1	M25x1,5	30	5,5	A1013.00.22.08
A8300.32.1	M32x1,5	36	6,0	A1021.00.30.08
A8300.40.1	M40x1,5	46	7,0	A1029.00.39.08
A8300.50.1	M50x1,5	55	7,0	A1036.00.49.08
A8300.63.1	M63x1,5	70	8,0	A1048.00.62.08

**Contre-écrous CEM dentés
pour un contact optimal**

**EMV-Gegenmuttern Messing
mit Schneidezähnen für eine
optimale Kontaktierung**

**EMC-lock-nuts
with cutting teeth
for optimised EMC contact**

Matière : laiton nickelé
Exécution : 6 pans (hexagonal)

Material: Messing vernickelt
Ausführung: 6-kant

Material: Nickel-plated brass
Type: hexagonal design

+200°C
-40°C



Référence
article



G




mm

M
mm

Filetage métrique

Gewinde metrisch

Thread metric



A8008.85	M 8x1,25	11	3,3
A8010.85	M10x1,5	13	3,3
A8012.85	M12x1,5	15	3,5
A8017.85	M16x1,5	18	3,5
A8020.85	M20x1,5	24	4,0
A8025.85	M25x1,5	30	4,0
A8032.85	M32x1,5	36	5,0
A8040.85	M40x1,5	46	5,3
A8050.85	M50x1,5	55	6,3
A8063.85	M63x1,5	70	7,0

Filetage Pg

Gewinde Pg

Thread Pg



A8007.85	Pg 7	15	3,3
A8009.85	Pg 9	18	3,3
A8011.85	Pg 11	21	3,5
A8013.85	Pg 13	24	3,5
A8016.85	Pg 16	24	3,5
A8021.85	Pg 21	30	4,0
A8029.85	Pg 29	38	4,6
A8036.85	Pg 36	50	5,8
A8042.85	Pg 42	55	5,8
A8048.85	Pg 48	65	6,5

Contre-écrous Polyamide**Gegenmuttern Kunststoff****Synthetic lock-nuts**

Matière : Polyamide chargé fibre de verre
Exécution : 6 pans (hexagonal)

Material: Polyamid glasfaserverstärkt
Ausführung: 6-kant

Material: Polyamide, glass-fiber reinforced
Type: hexagonal design

Couleur : gris clair = 5 RAL 7035
noir = 2 RAL 9005

Farbe: Hellgrau = 5 RAL 7035
Schwarz = 2 RAL 9005

Coulour: light grey = 5 RAL 7035
black = 2 RAL 9005

+100°C
-40°C



Référence
article




G



mm

M
mm

**Filetage métrique****Gewinde metrisch****Thread metric**

A8212	M12x1,5	17	5,5	5
A8217	M16x1,5	22	5,5	5
A8220	M20x1,5	26	6,5	5
A8225	M25x1,5	32	7,0	5
A8232	M32x1,5	41	7,0	5
A8240	M40x1,5	50	7,0	5
A8250	M50x1,5	60	8,5	5
A8263	M63x1,5	75	8,5	5

A8212.40	M12x1,5	17	5,5	2
A8217.40	M16x1,5	22	5,5	2
A8220.40	M20x1,5	26	6,5	2
A8225.40	M25x1,5	32	7,0	2
A8232.40	M32x1,5	41	7,0	2
A8240.40	M40x1,5	50	7,0	2
A8250.40	M50x1,5	60	8,5	2
A8263.40	M63x1,5	75	8,5	2

Filetage Pg**Gewinde Pg****Thread Pg**

A8207	Pg 7	19	5,5	5
A8209	Pg 9	22	5,5	5
A8211	Pg 11	24	5,0	5
A8213	Pg 13	27	6,0	5
A8216	Pg 16	30	6,0	5
A8221	Pg 21	36	7,5	5
A8229	Pg 29	46	7,5	5
A8236	Pg 36	60	8,5	5
A8242	Pg 42	65	8,5	5
A8248.48	Pg 48	70	8,5	5

A8207.40	Pg 7	19	5,5	2
A8209.40	Pg 9	22	5,5	2
A8211.40	Pg 11	24	5,0	2
A8213.40	Pg 13	27	6,0	2
A8216.40	Pg 16	30	6,0	2
A8221.40	Pg 21	36	7,5	2
A8229.40	Pg 29	46	7,5	2
A8236.40	Pg 36	60	8,5	2
A8242.40	Pg 42	65	8,5	2
A8248.48.40	Pg 48	70	8,5	2