

DB25S064T -
D-Subminiature : Cable
Connector 25 Way Socket
Solder Bucket, without
Accessory



OBSOLETE


www.fci.com

Alternate Products

DB25S064TLF

Specifications

General	
Contact type	Signal
Gender	Socket
Number of contacts (Total)	25
Orientation	Straight
Product Type	Connector
Termination Style	Solder Bucket
Dimensional	
Size (Shell)	B
Size (Wire)	20 AWG max. on Signal
Electrical	
Current rating	5A per Signal Contact
Resistance (Contact)	< 10 milli ohms
Voltage rating	300V rms at 50 Hz
Voltage rating (DWV - Dielectric withstanding)	1000V rms
Mechanical	
Durability (Mating cycles)	> 200 Cycles
Durability (Plating - Mating cycles)	Std Class (</=200 Mating Cycles)
Extraction force (Mating part)	0.3N min. per Contact
Extraction force (Signal)	0.3N min. per Contact
Insertion force (Mating part)	5N max. per Contact
Insertion force (Signal)	5N max. per Contact
Mounting	
Attachment	Cable
Mounting accessory	without Accessory
Mounting options	without Accessory
Physical	
Plating (Contact)	Gold over Nickel
Plating (Shell)	Semi Bright Nickel
Plating (Solder tail)	SnPb
Plating (Termination)	Tin-Lead over Nickel
Temperature (Range)	-55°C to +125°C
Approvals / Certifications	
Approvals / Certifications	Recognized (File E 118235)
Other Features	

Most Popular Configuration	Not Applicable
-----------------------------------	----------------