

IM Relay

- Slim line 10x6mm, low profile 5.65mm and min. board-space 60mm²
- Switching current 2/5A, switching power 60W/62.5VA and switching voltage 220VDC/250VAC
- Low coil power consumption, 140mW standard, 100mW for high sensitive version, 50mW for ultra high sensitive version and 100mW for bistable version
- High dielectric and surge capability up to 2500Vrms between open contacts and 2500Vrms between coil and contacts
- High mechanical shock resistance up to 50g functional

Typical applications

Telecommunication, access and transmission equipment, optical network terminals, modems, office and business equipment, consumer electronics, measurement and test equipment, industrial control, medical equipment, HVAC



Approvals

UL 508 File No. E 111441

Technical data of approved types on request

Contact Data	standard, C	D, I	P
	standard and high dielectric version	high current version	high contact stability version
Contact arrangement	2 form C, 2 CO		
Max. switching voltage	220VDC, 250VAC	220VDC, 250VAC	220VDC, 250VAC
Rated current	2A	5A	2A
Limiting continuous current	2A	5A	2A
Switching power	60W, 62.5VA		
Contact material	PdRu +Au	AgNi +Au	PdRu +Au
Contact style	covered twin cont.	covered twin cont.	covered twin cont.
	I: single contacts		
Minimum switching voltage	100µV		
Initial contact resistance	<50mΩ at 10mA/30mV I: < 100mΩ		
Thermoelectric potential	<10µV		
Operate time	typ. 1ms, max. 3ms		
Release time	typ. 1ms, max. 3ms		
without diode in parallel	typ. 3ms, max. 5ms		
with diode in parallel	typ. 1ms, max. 5ms		
Bounce time max.	typ. 1ms, max. 5ms		

Max. DC load breaking capacity



IM



Contact Data (continued)

Electrical endurance at contact application 0 ($\leq 30\text{mV}/\leq 10\text{mA}$)	min. 2.5×10^6 operations
cable load open end	min. 2.0×10^6 operations
resistive, 125VDC / 0.24A - 30W	min. 5×10^5 operations
resistive, 220 VDC / 0.27A - 60W	min. 1×10^5 operations
resistive, 250VAC / 0.25A - 62.5VA	min. 1×10^5 operations
resistive, 30VDC / 1A - 30W	min. 5×10^5 operations
resistive, 30VDC / 2A - 60W	min. 1×10^5 operations
UL contact rating	30VDC, 2A, 60W, NO only
	110VDC, 0.3A, 33W
	220VDC, 0.27A, 60W
	125VAC, 0.5A, 62.5W
	250VAC, 0.25A, 62.5W
Mechanical endurance	10^8 operations

Coil Data


Magnetic system	monostable, bistable
Coil voltage range	1.5 to 24VDC

Coil versions, standard version, monostable, 1 coil

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance $\Omega \pm 10\%$	Rated coil power mW
00	1.5	1.13	0.15	16	140
08	2.4	1.80	0.24	41	140
01	3	2.25	0.30	64	140
02	4.5	3.38	0.45	145	140
03	5	3.75	0.50	178	140
04	6	4.50	0.60	257	140
05	9	6.75	0.90	579	140
06	12	9.00	1.20	1029	140
07	24	18.00	2.40	2880	200

All figures are given for coil without pre-energization, at ambient temperature +23°C

Coil operating range, standard version



IM Relay (Continued)

Coil Data (continued)

Coil versions, sensitive version, monostable, 1 coil


Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance $\Omega \pm 10\%$	Rated coil power mW
11	3	2.40	0.30	91	100
12	4.5	3.60	0.45	194	100
13	5	4.00	0.50	234	100
16	12	9.60	1.20	1315	110
17	24	19.20	2.40	4120	140

Coil versions, ultra high sensitive version, monostable, 1 coil

Coil code	Rated voltage VDC	Operate voltage VDC	Release voltage VDC	Coil resistance $\Omega \pm 10\%$	Rated coil power mW
21	3	2.55	0.30	180	50
22	4.5	3.83	0.45	405	50
23	5	4.25	0.50	500	50
26	12	10.20	1.20	2880	50

All figures are given for coil without pre-energization, at ambient temperature +23°C

Coil operating range, sensitive and ultra high sensitive coil




Coil versions, standard, bistable 1 coil

Coil code	Rated voltage VDC	Set voltage VDC	Reset voltage VDC	Coil resistance $\Omega \pm 10\%$	Rated coil power mW
40	1.5	1.13	-1.13	23	100
48	2.4	1.80	-1.80	58	100
41	3	2.25	-2.25	90	100
42	4.5	3.38	-3.38	203	100
43	5	3.75	-3.75	250	100
44	6	4.50	-4.50	360	100
45	9	6.75	-6.75	810	100
46	12	9.00	-9.00	1440	100
47	24	18.00	-18.00	2880	200

All figures are given for coil without pre-energization, at ambient temperature +23°C

Coil operating range, bistable 1 coil



Insulation Data

	standard*	C*	D,P, I
	standard, sensitive, ultra high sensitive version	high dielectric version	high current, high contact stability version
Initial dielectric strength			
between open contacts	1000V _{rms}	1500V _{rms}	750V _{rms}
between contact and coil	1800V _{rms}	1800V _{rms}	1500V _{rms}
between adjacent contacts	1000V _{rms}	1800V _{rms}	750V _{rms}
Initial surge withstand voltage			
between open contacts	1500V	2500V	1000V
between contact and coil	2500V	2500V	2000V
between adjacent contacts	1500V	2500V	1000V
Initial insulation resistance			
between insulated elements	>10 ⁹ Ω	>10 ⁹ Ω	>10 ⁹ Ω
Capacitance			
between open contacts		max. 1pF	
between contact and coil		max. 2pF	
between adjacent contacts		max. 2pF	

*this relay contains SF6 (Sulfur hexafluoride, CAS number: 2551-62-4) for dielectric strength enhancement, SF6 is hermetically sealed in relay without leaks to air during normal application as recommended per the applicable product specification. It is clarified that the usage of SF6 in mini signal relay is not prohibited by related regulations. Please contact TE local sales or field engineer for further information and detailed material declaration.

RF Data


Isolation at 100MHz/900MHz	37.0dB/18.8dB
Insertion loss at 100MHz/900MHz	0.03dB/0.33dB
Voltage standing wave ratio (VSWR) at 100MHz/900MHz	1.06/1.49

Other Data

Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at www.te.com/customer-support/rohssupportcenter

Ambient temperature	-40°C to +85°C
Thermal resistance	<150K/W
Category of environmental protection	IEC 61810
	RT V - hermetically sealed
Vibration resistance (functional)	20g, 10 to 500Hz
Shock resistance (functional), half sinus 11ms	50g
Shock resistance (destructive), half sinus 0.5ms	500g
Mounting position	any
Weight	max. 0.75g
Resistance to soldering heat SMT	IEC 60068-2-58
Moisture sensitive level, JEDEC J-Std-020D	MSL3
related only to SMT relays	
packed in original dry-packs	

Ultrasonic cleaning	not recommended
Packaging/unit	tube/50pcs., box/1000 pcs.
Terminal assignment	reel/1000 pcs., box/1000 or 5000 pcs.
TOB version relay	Bistable version, 1 coil
Monostable version	reset condition




Contacts are shown in reset condition. Contact position might change during transportation and must be reset before use.


IM Relay (Continued)

Dimensions

THT version




SMT version



PCB layout


TOP view on component side of PCB




Processing

Recommended soldering conditions

Recommended reflow soldering profile IEC 61760-1





Resistance to soldering heat - reflow profile IEC 60068-2-58




IM Relay (Continued)

Packing


Tube for THT version
50 relays per tube, 1000 relays per box



Tape and reel for SMT version
1000 relays per reel, 1000 or 5000 relays per box



Reel dimensions



Product code structure

Typical product code

IM

03

G

R

Type

IM Signal Relays IM Series

Contact arrangement

Blank 2 form C, 2 CO

Coil

Coil code: please refer to coil versions table

Performance type

Blank Standard version

I High current version HVAC
C High dielectric version
D High current version
P High contact stability version

Terminals

T THT - standard
N THT - narrow version

J SMT - J-leg
G SMT - gull wing

Packing

S Tube

R Reel

IM Relay (Continued)

Product code	Arrangement	Perf. type	Coil	Coil type	Coil	Terminals	Part number	
IM00GR	2 form C, 2 CO contacts	Standard	1.5VDC	Monostable	Standard	SMT gull wing	3-1462037-7	
IM00JR						SMT J-leg	3-1462037-9	
IM00NS			3VDC			THT narrow	1-1462038-0	
IM01GR						SMT gull wing	1462037-1	
IM01JR	SMT J-leg	4-1462037-0						
IM01NS	THT narrow	1-1462038-1						
IM01TS	4.5VDC			THT standard	1462037-4			
IM02GR				SMT gull wing	1462037-9			
IM02JR				SMT J-leg	1-1462037-1			
IM02NS				THT narrow	1-1462038-2			
IM03GR	5VDC			SMT gull wing	1-1462037-4			
IM03JR				SMT J-leg	1-1462037-6			
IM03NS				THT narrow	1-1462038-3			
IM03TS				THT standard	1-1462037-8			
IM04GR	6VDC			SMT gull wing	4-1462037-2			
IM04JR				SMT J-leg	4-1462037-4			
IM04NS				THT narrow	1-1462038-4			
IM05GR				SMT gull wing	3-1462037-4			
IM05JR	9VDC			SMT J-leg	4-1462037-5			
IM05NS				THT narrow	1-1462038-5			
IM05TS				THT standard	2-1462037-2			
IM06GR				SMT gull wing	2-1462037-3			
IM06JR	12VDC			SMT J-leg	4-1462037-6			
IM06NS				THT narrow	1-1462038-6			
IM07GR				24VDC			SMT gull wing	4-1462037-7
IM07JR							SMT J-leg	4-1462037-8
IM07NS	THT narrow	1-1462038-7						
IM08GR	2.4VDC	High sens.	SMT gull wing				6-1462039-3	
IM11GR	3VDC			9-1462038-5				
IM12GR	4.5VDC			1462039-3				
IM13GR	5VDC			1462039-4				
IM16GR	12VDC	1462039-5						
IM17GR	24VDC			1462039-6				
IM17TS				THT standard	4-1462039-6			
IM21GR	3VDC			Ultra high sensitive	SMT gull wing	2-1462039-6		
IM21TS					THT standard	1-1462039-5		
IM22GR	4.5VDC	SMT gull wing	2-1462039-7					
IM22TS		THT standard	2-1462039-8					
IM23GR	5VDC			SMT gull wing	2-1462039-9			
IM23TS				THT standard	3-1462039-0			
IM26GR	12VDC			SMT gull wing	3-1462039-1			
IM26TS				THT standard	3-1462039-2			
IM40GR	1.5VDC		Bistable	Standard	SMT gull wing	5-1462037-1		
IM40JR					SMT J-leg	5-1462037-2		
IM40NS					3VDC	THT narrow	1-1462038-8	
IM40TS						THT standard	5-1462037-0	
IM41GR	3VDC			SMT gull wing	5-1462037-4			
IM41JR				SMT J-leg	5-1462037-5			
IM41NS				THT narrow	1-1462038-9			
IM41TS				THT standard	5-1462037-3			
IM42GR	4.5VDC			SMT gull wing	3-1462037-1			
IM42JR				SMT J-leg	5-1462037-7			
IM42NS				THT narrow	2-1462038-0			
IM42TS				THT standard	5-1462037-6			
IM43GR	5VDC			SMT gull wing	5-1462037-9			
IM43JR				SMT J-leg	6-1462037-0			
IM43NS				THT narrow	2-1462038-1			
IM43TS				THT standard	5-1462037-8			
IM44GR	6VDC			SMT gull wing	6-1462037-2			
IM44JR				SMT J-leg	6-1462037-3			
IM44NS				THT narrow	2-1462038-2			
IM44TS				THT standard	6-1462037-1			
IM45GR	9VDC			SMT gull wing	6-1462037-4			
IM45JR				SMT J-leg	6-1462037-5			
IM45NS				THT narrow	2-1462038-3			
IM46GR				12VDC	SMT gull wing	6-1462037-7		
IM46JR				SMT J-leg	6-1462037-8			
IM46NS				THT narrow	2-1462038-4			
IM46TS				THT standard	6-1462037-6			
IM47GR				24VDC	SMT gull wing	7-1462037-0		
IM47JR				SMT J-leg	7-1462037-1			
IM47NS				THT narrow	2-1462038-5			
IM47TS				THT standard	6-1462037-9			
IM48GR				2.4VDC	SMT gull wing	1462039-8		

IM Relay (Continued)

Product code	Arrangement	Perf. type	Coil	Coil type	Coil	Terminals	Part number
IM01CGR	2 form C	High	3VDC	Monostable	Standard	SMT gull wing	1462038-4
IM01CTS	2 CO	dielectric				THT standard	9-1462038-6
IM02CGR	contacts		4.5VDC			SMT gull wing	1462038-1
IM03CGR			5VDC				1462038-2
IM03CJR						SMT J-leg	4-1462039-8
IM03CTS						THT standard	4-1462039-7
IM05CGR			9VDC			SMT gull wing	1462038-3
IM06CGR			12VDC				9-1462037-9
IM06CJR						SMT J-leg	3-1462039-4
IM06CTS						THT standard	4-1462037-9
IM07CGR			24VDC			SMT gull wing	1462039-2
IM07CTS						THT standard	1462039-1
IM17CGR					High sens.	SMT gull wing	1462039-7
IM41CGR			3VDC	Bistable	Standard		4-1462039-2
IM42CGR			4.5VDC				4-1462039-1
IM43CGR			5VDC				9-1462038-7
IM02DGR		High	4.5VDC	Monostable	Standard		9-1462038-8
IM03DGR		current	5VDC				9-1462038-9
IM03DJR						SMT J-leg	3-1462039-3
IM05DGR			9VDC			SMT gull wing	1-1462039-7
IM06DGR			12VDC				1-1462039-8
IM06DJR						SMT J-leg	7-1462039-0
IM06DTS						THT standard	3-1462039-8
IM07DGR			24VDC			SMT gull wing	3-1462039-7
IM07DJR						SMT J-leg	7-1462039-4
IM07DTS						THT standard	7-1462039-2
IM22DTS			4.5VDC		U.h.sens.		7-1462039-6
IM41DGR			3VDC	Bistable	Standard	SMT gull wing	6-1462039-8
IM42DGR			4.5VDC				1-1462039-9
IM42DNS						THT narrow	1-1462039-6
IM46DNS			12VDC				1-1462039-2
IM47DJR			24VDC			SMT J-leg	7-1462039-5
IM48DGR			2.4VDC			SMT gull wing	1462039-9
IM49DGR			2VDC				2-1462039-2
IM48IGR			2.4VDC				1462047-1
IM49IGR			2VDC				1462047-4
IM02PGR		High	4.5VDC	Monostable	Standard		5-1462039-4
IM02PNS		contact				THT narrow	5-1462039-8
IM03PGR		stability	5VDC			SMT gull wing	5-1462039-5
IM03PJR						SMT J-leg	6-1462039-6
IM03PNS						THT narrow	5-1462039-9
IM06PGR			12VDC			SMT gull wing	5-1462039-6
IM06PNS						THT narrow	6-1462039-0
IM42PGR			4.5VDC	Bistable	Standard	SMT gull wing	5-1462039-7
IM42PNS						THT narrow	7-1462039-8
IM43PGR						SMT gull wing	7-1462039-3
IM46PNS			12VDC			THT narrow	6-1462039-1