

Fuseholder Open Design, Holder for MSB and 172876, THT



125 VAC/DC · 0.9 W (UL/CSA)

**Description**

- Surface Mount Device

Standards

- UL 4248-1 / UL 512
 - CSA C22.2 no. 39

Approvals

- UL File Number: E41738
 - CSA File Number: 23151



References[Packaging Details](#)**Weblinks**

[pdf](#), [html](#), [General Product Information](#), [Approvals](#), [RoHS](#), [CHINA-RoHS](#),
[e-Store](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data

Fuse-Link	2 x 7 mm
Mounting	PCB
Terminal	Solder SMT
Rated Voltage	125 VAC/DC
Rated Power Acceptance IEC	0.9 W @ Ta 23 °C
Degree of Protection	IP 00
Admissible Ambient Air Temp.	-40 °C to 85 °C
Climatic Category	40/085/21 acc. to IEC 60068-1
Material: Socket	Thermoplastic, black, UL 94V-0
Material: Terminals	Tin-Plated Bronze
Unit Weight (Socket/Cap)	0.45 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	 Approvals

Soldering Methods	Reflow
Solderability	245 °C / 3 sec acc. to IEC 60068-2-20, Test Td
Resistance to Soldering Heat	260 °C / 10 sec acc. to IEC 60068-2-20, Test Td

Abmessungen
 14 mm


Soldering pads

Variants

Holder	Order Number
●	7090.9010.xx

Packaging Unit

.xx = .03 Plastic Bag (100 pcs.)
 .xx = .55 Blister Tape (500 pcs.)