

Cover for Holder OGN, OGN-SMD



4W/10A

**Standards**

- IEC 60127-6
- UL 4248-1 / UL 512
- CSA C22.2 no. 39

Approvals

- VDE Certificate Number: 4001042
- UL File Number: E39328

References

Fits to type:

Weblinks



[pdf](#), [html](#), [General Product Information](#), [Approvals](#), [RoHS](#), [CHINA-RoHS](#), [e-Store](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data

Fuse-Link	5 x 20 mm
Rated Power Acceptance IEC	4W / 10A @ Ta 23°C
	2.5 W / 10 A with transparant cover, see derating curves
Admissible Ambient Air Temp.	-40°C to 85°C
Storage Conditions	0°C to 60°C, max. 70% r.h.

Abmessungen

25 mm



Variants 0853.0551, 0853.0571, 0853.0573 and 0853.0575

Variant 0853.0576

Variants

Description	Order Number
Transparent Cover	0853.0551
Reflow-Cover	0853.0571
Cover, black, meets IEC 60335-1 Ed. 4.0	0853.0575
Reflow-Cover with Clamp	0853.0576

Packaging Unit

Plastic Bag (100 pcs.)