Number of contacts

7 + ⏚

Identification	Part number Male insert (M)	Part number Female insert (F)	Drawing	Dimensions in mm
Crimp terminal Order crimp contacts separately	**09 12 007 3001**	**09 12 007 3101**	 Contact arrangement view from termination side	
Coding pins	09 12 000 9901	09 12 000 9902		

Identification	Wire gauge (mm²)	Part number Male contact	Part number Female contact	Drawing	Dimensions in mm
Crimp contacts Power contacts silver plated	0.14-0.37	**09 15 000 6104**	**09 15 000 6204**		
	0.5	**09 15 000 6103**	**09 15 000 6203**		
	0.75	**09 15 000 6105**	**09 15 000 6205**		
	1	**09 15 000 6102**	**09 15 000 6202**		
	1.5	**09 15 000 6101**	**09 15 000 6201**		
	2.5	**09 15 000 6106**	**09 15 000 6206**		
gold plated	0.14-0.37	**09 15 000 6124**	**09 15 000 6224**		
	0.5	**09 15 000 6123**	**09 15 000 6223**		
	0.75	**09 15 000 6125**	**09 15 000 6225**		
	1	**09 15 000 6122**	**09 15 000 6222**		
	1.5	**09 15 000 6121**	**09 15 000 6221**		
	2.5	**09 15 000 6126**	**09 15 000 6226**		
F.O. contacts for 1 mm plastic fibre		20 10 001 3211	20 10 001 3221		

Wire gauge			∅	Stripping length
0.14-0.37	mm²	AWG 26-22	0.9	8 mm
0.5	mm²	AWG 20	1.1	8 mm
0.75	mm²	AWG 18	1.3	8 mm
1	mm²	AWG 18	1.45	8 mm
1.5	mm²	AWG 16	1.75	8 mm
2.5	mm²	AWG 14	2.25	6 mm

Stock items in bold type