



Serre-câbles DM-SES®
en Polyamide 6 noir et blanc
pour blocage des câbles




DM-SES®


-20 à +70°C



type	code article	code article		dimensions des câbles (mm)		dimensions (mm)					
	010	001		isolant PVC	isolant caoutchouc	A	B	logement a b		C	
câbles ronds											
DM 2	0131 0012 010	0131 0012 001	100	Ø 3 ... 4,5	Ø 3 ... 4,5	9,5	8,5	1,7	10,3	11	
DM 2L	0131 0032 010	0131 0032 001	100	Ø 3 ... 4,5	Ø 3 ... 4,5	9,5	8,5	3,1	10,3	11	
DM 4	0131 0001 010	0131 0001 001	100	Ø 5 ... 6,5	Ø 5 ... 7	13,0	11,5	2,5	12,0	14	
DM 5	0131 0010 010	0131 0010 001	100	Ø 6,5... 7,5	Ø 6,5 ... 7,5	13,0	11,5	2,5	11,0	14	
DM 6	0131 0002 010	0131 0002 001	100	Ø 6,6 ... 8	Ø 7,1 ... 9	16,0	14,0	3,0	17,0	18	
DM 7	0131 0003 010	0131 0003 001	100	Ø 8,1...10	Ø 9,1 ... 11	22,5	21,0	3,0	20,0	25	
DM 8	0131 0004 010	0131 0004 001	100	Ø 10,1...12,5	Ø 11,1...14	22,5	21,0	3,5	22,0	25	
câbles méplats											
DM 2P	0131 0022 010	0131 0022 001	100	3 x 5	3 x 5	9,5	8,5	1,7	10,3	11	
DM 2LP	0131 0042 010	0131 0042 001	100	3 x 5	3 x 5	9,5	8,5	3,1	10,3	11	
DM 4P	0131 0020 010	0131 0020 001	100	3 x 7,6	3,8 x 7,1	13,0	11,5	2,8	10,5	14	
DM 6P	0131 0021 010	0131 0021 001	100	5 x 9	5 x 9	16,0	14,0	3,0	17,0	18	



Pour un logement circulaire (ØA).
Pour un blocage en rotation du
serre-câble, le logement à pans
(B) est nécessaire.



principe de blocage
du câble

outils de montage : voir page suivante