# **Data Sheet**

# Coaxial PCB Connector 85\_BNC-50-0-1/133\_N



### **Description**

Right angle PCB jack

Interface Standards IEC 60169-8\_MIL-STD-348A/301\_CECC 22120



#### **Technical Data**

**Electrical Data** 

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 4 \ \text{GHz} \end{array}$ 

**Mechanical Data** 

Board mounting type through holes Weight 0.0187 kg

**Environmental Data** 

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

### **Material Data**

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

#### **Related Documents**

 Outline drawing
 DOU-00070952

 Catalogue drawing
 DCA-00012658

 Mounting hole
 DOU-00012084

### **Ordering Information**

Single package 85\_BNC-50-0-1/133\_NE

## **Remarks**

PCB connector with stand-offs

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.