

LOC		DIST		REVISIONS					
—		—		P	LTR	DESCRIPTION	DATE	DWN	APVD
NUMMER 825440					F	WERKSTOFF GEÄNDERT	15.07.97	—	A.ZITZ
VERWENDET FÜR E 92-9802					F1	REVISED PER ECO-09-023313	09OCT09	—	AEG
WAR NR. —					F2	ECR-10-022530	11JAN11	KK	HMR
				CAD-ORIGINAL ZEICHNUNG NICHT ÄNDERN					

POLZ. PRO REIHE	L±0.5	BESTELL-NR.	
—	—	—	
2	5.08	825 440	-2
3	7.62		-3
4	10.16		-4
5	12.70		-5
6	15.24		-6
7	17.78		-7
8	20.32		-8
9	22.86		-9
10	25.40	1-	-0
11	27.94	1-	-1
12	30.48	1-	-2
13	33.02	1-	-3
14	35.56	1-	-4
15	38.10	1-	-5
16	40.64	1-	-6
17	43.18	1-	-7
18	45.72	1-	-8
19	48.26	1-	-9
20	50.80	2-	-0
21	53.34	2-	-1
22	55.88	2-	-2
23	58.42	2-	-3
24	60.96	2-	-4
25	63.50	2-	-5
26	66.04	2-	-6
27	68.58	2-	-7
28	71.12	2-	-8
29	73.66	2-	-9
30	76.20	3-	-0
31	78.74	3-	-1
32	81.28	3-	-2
33	83.82	3-	-3
34	86.36	3-	-4
35	88.90	3-	-5
36	91.44	3-	-6
37	93.98	3-	-7
38	96.52	3-	-8
39	99.06	3-	-9
40	101.60	4-	-0
41	104.14	4-	-1
42	106.68	4-	-2
43	109.22	4-	-3
44	111.76	4-	-4
45	114.30	4-	-5
46	116.84	4-	-6
47	119.38	4-	-7
48	121.92	4-	-8
49	124.46	4-	-9
50	127.00	5- 825 440	-0

STECKSEITE: IM BEREICH "F" 0.8µm GOLD ÜBER 1.27 µm NICKEL
LÖTSEITE: MIN. 2.5 µm ZINN ÜBER 1.27 µm NICKEL

KONTAKTSTIFT	Cu Sn	△
STIFTGEHÄUSE	PBT GV	GRÜN
BENENNUNG	WERKSTOFF	OBERFLÄCHE FARBE

ZEICHNUNG GÜLTIG AB KW 39./96

DIMENSIONS:		DWN 22.06.84	MATERIAL	FINISH
mm		M.SCHAARSCHMIDT	—	—
TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK —	TE Connectivity	
±0.2 mm		APVD —		
0 PLC ± —		PRODUCT SPEC —		
1 PLC ± —		APPLICATION SPEC —		
2 PLC ± —		WEIGHT —	NAME	AMPMODU II STIFTLEISTE ZWEIREIHIG
3 PLC ± —			SIZE	CAGE CODE
4 PLC ± —			DRAWING NO	RESTRICTED TO
ANGLES ± —			A4 00779	—
			C-825440	
			CUSTOMER DRAWING	SCALE 4:1
				SHEET 1 OF 2
				REV F2

LOC —	DIST —	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
			—	SEE SHEET 1	—	—	—

VERWENDET FÜR
E 92-9802

WAR NR. —

CAD-ORIGINAL
ZEICHNUNG NICHT ÄNDERN

Polz. pro Reihe	L±0.5	Bestell-Nr.		Bemerkung
1	2.54	5-	-1	
2	5.08	5-	-2	
3	7.62	5-	-3	
4	10.16	5-	-4	
5	12.70	5-	-5	
6	15.24	5-	-6	
7	17.78	5-	-7	
8	20.32	5-	-8	
9	22.86	5-	-9	
10	25.40	6-	0	
11	27.94	6-	-1	
12	30.48	6-	-2	
13	33.02	6-	-3	
14	35.56	6-	-4	
15	38.10	6-	-5	
16	40.64	6-	-6	
17	43.18	6-	825 440 -7	△
18	45.72	6-	-8	
19	48.26	6-	-9	
20	50.80	7-	0	

△ VERPACKUNG:25 STÜCK IN PLASTIK-DOSE
PN 165 439-1 MIT PLASTIK-DECKEL
PN 165 440-1

△ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

△ OBSOLETE

BENENNUNG		WERKSTOFF	OBERFLÄCHE
			FARBE

ZEICHNUNG GÜLTIG AB KW 39/96

DIMENSIONS: mm		DWN A.HO 07.06.84	MATERIAL —	FINISH —		
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± — 1 PLC ± — 2 PLC ± — 3 PLC ± — 4 PLC ± — ANGLES ± —		CHK M.SCHAARSCHMIDT 13.06.84	TE TE Connectivity			
		APVD —				
		PRODUCT SPEC —				
		APPLICATION SPEC —	NAME AMPMODU II STIFTLEISTE ZWEIREIHIG			
		WEIGHT —	SIZE A4	CAGE CODE 00779	DRAWING NO C-825440	RESTRICTED TO —
CUSTOMER DRAWING			SCALE 4:1	SHEET 2 OF 2	REV F2	

RELEASED FOR PUBLICATION

THIS DRAWING IS UNPUBLISHED.

ALL RIGHTS RESERVED.

By -
COPYRIGHT -