



Douilles cylindriques renforcées (existent en version non renforcée PVC)

Ref.	Section	Mesures (mm)					
	mm ² /AWG	B	b	L	D	E	
PVCC-15039	0.25-1.65 22-16	4.00	5.80	24.00	4.70	10.50	100/1000
PVCC-25039	1.04-2.63	4.00	6.20	24.50	4.90	11.00	100/1000
PVCC-25049	16-14	5.00	6.20	24.50			
PVCC-55039	2.63-6.64	4.00	8.20	28.00	6.50	14.00	50/500
PVCC-55049	12-10	5.00	8.20	28.00			



Raccords renforcés

Ref.	Section	Mesures (mm)				
	mm ² /AWG	ØC	ØD	L		
PVCC-15017-EF	0.25-1.65 22-16	1.80	4.20	26.20	100/1000	
PVCC-25023-EF	1.04-2.63 16-14	2.70	5.00	27.30	100/1000	
PVCC-55034-EF	2.63-6.64 12-10	3.40	6.80	31.50	50/500	



Embouts préisolés thermorétractables

Ref.	Section	Mesures (mm)		
	mm ² /AWG	d2	L	
SB-2218	0.25-0.75 22-18	1.40	25.00	100/1000
SB-1816	0.50-1.50 22-16	1.70	36.00	100/1000
SB-1614	1.50-2.50 16-14	2.30	36.00	100/500
SB-1210	4.00-6.00 12-10	3.40	41.00	25/250



Embouts à souder thermorétractables

Ref.	Section	Mesures (mm)			
	cables mm ²	L Max.	ID Min.		
SBS-91	0.3 a 0.8	26.0	1.7	50/500	
SBS-92	0.8 a 2.0	42.0	2.7	50/500	
SBS-93	2.0 a 4.0	42.0	4.5	50/500	
SBS-94	4.0 a 6.0	42.0	6.0	25/250	
SBS-95	6.0 a 10.0	42.0	7.0	25/250	



Embouts à souder thermorétractables

Ref.	Section	Mesures (mm)				
	mm ² /AWG	ØC	ØD	L		
SBS-0.5	0.50-1.00 22-18	2.50	3.50	25.00	100/1000	
SBS-1	0.50-1.50 22-16	4.23	5.50	37.00	100/500	
SBS-2	1.50-2.50 16-14	4.70	6.40	37.00	100/500	
SBS-5	4.00-6.00 12-10	7.10	8.00	42.00	50/250	

