

Contre-écrous en laiton nickelé



Contre-écrous laiton

Matière : laiton nickelé

Exécution : 6 pans


Températures d'utilisation : -40 à +200°C



Référence article	 G	 mm	M
			mm

Filetage métrique

A8000.06.1	M 6x0,75	9	2,8
A8000.06	M 6x1,0	9	2,8
A8000.08.1	M 8x1,0	11	2,8
A8000.08	M 8x1,25	11	2,8
A8000.10.1	M 10x1,0	13	2,8
A8000.10	M 10x1,5	13	2,8
A8000.12	M 12x1,5	15	3,0
A8000.17	M 16x1,5	19	3,0
A8000.20	M 20x1,5	24	3,5
A8000.25	M 25x1,5	30	4,0
A8000.32	M 32x1,5	36	4,0
A8000.40	M 40x1,5	46	5,0
A8000.50	M 50x1,5	55	5,5
A8000.63	M 63x1,5	70	6,0
A8000.75	M 75x1,5	80	6,0
A8000.080	M 80x2,0	95	8,0
A8000.085	M 85x2,0	95	8,0
A8000.095	M 95x2,0	110	9,0
A8000.100	M100x3,0	115	9,0
A8000.105	M105x3,0	120	9,0
A8000.115	M115x3,0	125	10,0



Filetage Pg

A8007	Pg 7	15	3,0
A8009	Pg 9	18	3,0
A8011	Pg 11	21	3,0
A8013	Pg 13	23	3,0
A8016	Pg 16	26	3,0
A8021	Pg 21	32	3,5
A8029	Pg 29	41	4,0
A8036	Pg 36	51	5,0
A8042	Pg 42	60	5,0
A8048.48	Pg 48	64	5,5

Filetage gaz

A803/8G	G 3/8"	19	3,0
A801/2G	G 1/2"	24	3,0
A805/8G	G 5/8"	26	3,0
A803/4G	G 3/4"	30	3,5
A801G	G 1"	38	4,5
A8011/4G	G 1 1/4"	46	5,0
A8011/2G	G 1 1/2"	51	5,0
A8048	G 2"	64	5,5

Contre-écrous en acier inoxydable



Contre-écrous inox

Matière : INOX 303
DIN 1.4305 / CrNi A2

Exécution : 6 pans


Températures d'utilisation : -40 à +300°C



Référence article			M
	G	mm	mm

Filetage métrique

A8008.96	M 8x1,25	11	2,8
A8010.96	M 10x1,5	13	2,8
A8012.96	M 12x1,5	17	3,0
A8017.96	M 16x1,5	19	3,0
A8020.96	M 20x1,5	24	3,5
A8025.96	M 25x1,5	30	3,5
A8032.96	M 32x1,5	36	4,5
A8040.96	M 40x1,5	46	4,5
A8050.96	M 50x1,5	55	5,5
A8063.96	M 63x1,5	70	6,0



Filetage Pg

A8007.96	Pg 7	17	3,5
A8009.96	Pg 9	19	3,5
A8011.96	Pg 11	22	3,5
A8013.96	Pg 13	24	4,0
A8016.96	Pg 16	27	4,0
A8021.96	Pg 21	32	4,5
A8029.96	Pg 29	41	5,5
A8036.96	Pg 36	51	6,0

Matière : INOX 316
DIN 1.4435 / CrNiMo A4

Exécution : 6 pans

Températures d'utilisation : -40 à +300°C

Référence article			M
	G	mm	mm

Filetage métrique

A8008.98	M 8x1,25	11	2,8
A8010.98	M10x1,5	13	2,8
A8012.98	M12x1,5	17	3,0
A8017.98	M16x1,5	19	3,0
A8020.98	M20x1,5	24	3,5
A8025.98	M25x1,5	30	3,5
A8032.98	M32x1,5	36	4,5
A8040.98	M40x1,5	46	4,5
A8050.98	M50x1,5	55	5,5
A8063.98	M63x1,5	70	6,0

Contre-écrous spéciaux



Contre-écrous épais

Matière : laiton nickelé

Exécution : 6 pans, type épais


Températures d'utilisation : -40 à +200°C



Référence article	 G	 mm	M mm
-------------------	---	--	------

Filetage métrique

A8300.12	M 12x1,5	15	5,0
A8300.17	M 16x1,5	19	5,0
A8300.20	M 20x1,5	24	5,5
A8300.25	M 25x1,5	30	5,5
A8300.32	M 32x1,5	36	6,0
A8300.40	M 40x1,5	46	7,0



Filetage Pg

A8300.07	Pg 7	15	5,0
A8300.09	Pg 9	18	5,0
A8300.11	Pg 11	21	5,0
A8300.13	Pg 13	24	5,5
A8300.16	Pg 16	26	5,5
A8300.21	Pg 21	32	6,0
A8300.29	Pg 29	41	7,0


Contre-écrous à gorge

Matière : laiton nickelé

Exécution : 6 pans, à gorge par joint torique

Joint torique : à commander séparément


Températures d'utilisation : -40 à +200°C



Référence article	 G	 mm	M mm	Code joint torique
-------------------	---	--	------	--------------------

Filetage métrique

A8300.12.1	M12x1,5	15	5,0	A1007.00.08
A8300.17.1	M16x1,5	19	5,0	A1016.00.15.08
A8300.20.1	M20x1,5	24	5,5	A1016.00.08
A8300.25.1	M25x1,5	30	5,5	A1013.00.22.08
A8300.32.1	M32x1,5	36	6,0	A1021.00.30.08
A8300.40.1	M40x1,5	46	7,0	A1029.00.39.08
A8300.50.1	M50x1,5	55	7,5	A1036.00.49.08
A8300.63.1	M63x1,5	70	8,0	A1048.00.62.08





Contre-écrous CEM

Matière : laiton nickelé

Exécution : 6 pans, dents pour contact optimal


Températures d'utilisation : -40 à +200°C



Référence article	 G	 mm	M mm
----------------------	--	---	---------

Filetage métrique

A8008.85	M 8x1,25	11	3,3
A8010.85	M10x1,5	13	3,3
A8012.85	M12x1,5	15	3,5
A8017.85	M16x1,5	19	3,5
A8020.85	M20x1,5	24	4,0
A8025.85	M25x1,5	30	4,0
A8032.85	M32x1,5	36	5,0
A8040.85	M40x1,5	46	5,3
A8050.85	M50x1,5	55	6,3
A8063.85	M63x1,5	70	7,0



Filetage Pg

A8007.85	Pg 7	15	3,3
A8009.85	Pg 9	18	3,3
A8011.85	Pg 11	21	3,5
A8013.85	Pg 13	24	3,5
A8016.85	Pg 16	26	3,5
A8021.85	Pg 21	32	4,0
A8029.85	Pg 29	41	4,6
A8036.85	Pg 36	50	5,8
A8042.85	Pg 42	60	5,8
A8048.85	Pg 48	64	6,5