

Contre-écrous en laiton nickelé**Gegenmuttern Messing****Lock-nuts nickel-plated brass**

Matière : laiton nickelé
Exécution : 6 pans (hexagonal)

Material: Messing vernickelt
Ausführung: 6-kant

Material: Nickel-plated brass
Type: hexagonal design

+200°C
-40°C



Référence
article



G



mm

M
mm

Filetage métrique**Gewinde metrisch****Thread metric**

A8000.06.1	M	6x0,75	9	2,8
A8000.06	M	6x1,0	9	2,8
A8000.08.1	M	8x1,0	11	2,8
A8000.08	M	8x1,25	11	2,8
A8000.10.1	M	10x1,0	13	2,8
A8000.10	M	10x1,5	13	2,8
A8000.12	M	12x1,5	15	3,0
A8000.17	M	16x1,5	19	3,0
A8000.20	M	20x1,5	24	3,5
A8000.25	M	25x1,5	30	4,0
A8000.32	M	32x1,5	36	4,5
A8000.40	M	40x1,5	46	4,0
A8000.50	M	50x1,5	55	5,5
A8000.63	M	63x1,5	70	6,0
A8000.75	M	75x1,5	80	6,0
A8000.085	M	85x2,0	95	8,0
A8000.095	M	95x2,0	110	9,0
A8000.100	M	100x3,0	115	9,0
A8000.105	M	105x3,0	120	9,0
A8000.115	M	115x3,0	125	10,0

Filetage Pg**Gewinde Pg****Thread Pg**

A8007	Pg	7	15	2,8
A8009	Pg	9	18	2,8
A8011	Pg	11	21	3,0
A8013	Pg	13	23	3,0
A8016	Pg	16	26	3,0
A8021	Pg	21	32	3,5
A8029	Pg	29	41	4,0
A8036	Pg	36	51	5,0
A8042	Pg	42	60	5,0
A8048.48	Pg	48	64	5,5

Filetage au pas gaz**Gasrohr - Gewinde****Thread gas-pipe**

A80 ^{3/8}	G	G 3/8"	19	3,0
A80 ^{1/2}	G	G 1/2"	24	3,0
A80 ^{5/8}	G	G 5/8"	26	3,0
A80 ^{3/4}	G	G 3/4"	30	3,5
A801	G	G 1"	38	4,5
A801 ^{1/4}	G	G 1 1/4"	46	5,0
A801 ^{1/2}	G	G 1 1/2"	51	5,0
A8048	G	G 2"	64	5,5