

HUBER+SUHNER® DATA SHEET

Coaxial Panel Connector: 22_SMA-50-0-12/111_N

Rev.: F



Description

Straight bulkhead receptacle jack

Interface standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Weight 0.0031 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) not compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Gasket

Material

Copper Beryllium Alloy
Copper Beryllium Alloy
Copper Beryllium Alloy
PFA / PTFE
FPM

Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)

Related Documents

Catalogue drawing DCA-00011406
Mounting hole DOU-00010146

Ordering Information

Tray package 22_SMA-50-0-12/111_NY
Single package 22_SMA-50-0-12/111_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com