Data Sheet

Coaxial Cable Connector 11_MBX-50-2-1/113_N

Description

Straight cable plug

Interface standards HUBER+SUHNER MBX





Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	6 GHz	
Mechanical Data		
Centre contact	crimped	
Outer 2contact	crimped	
Weight	0.003546 kg	
	0.0000.0.19	
Environmental Data		
Operating temperature	-55 °C to 155 °C	
2011/65/EU (RoHS)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Bronze / Brass	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	

Related Documents

Outline drawing	DOU-00162030	
Catalogue drawing	DCA-00161650	
Assembly instruction	DOC-0000333519	
Ordering Information		
Bulk 100 pcs package	11_MBX-50-2-1/113_NH	

Additional Information

Suitable cables

ENVIROFLEX_316_D, K_02252_D, G_02232_D

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.



