

Disques d'obturation

Bouche-trous

Joint sectionnables



Disques

Matière : PA
Protection anti-poussière pour presse-étoupe.

Températures d'utilisation : -20 à +100°C

Référence article	 G	Ø mm	 mm
A1012.00.19	M10/M12/Pg7	10,5	0,3
A1017.00.19	M16/Pg9	13,5	0,3
A1011.00.19	Pg 11	16,5	0,3
A1020.00.19	M20/Pg13/Pg16	20,5	0,3
A1025.00.19	M25/Pg21	26,5	0,3
A1029.00.19	Pg29	35,0	0,3
A1032.00.19	M32	30,0	0,3
A1036.00.19	Pg36	45,0	0,3
A1040.00.19	M40	38,0	0,3
A1050.00.19	M50/Pg42	52,0	0,3
A1063.00.19	M63/Pg48	57,0	0,3



Bouche-trous

Matière : PA
Permettent d'obturer les perçages non utilisés des joints.

Températures d'utilisation : -30 à +100°C

Référence article	Ø mm	H mm
A1310.030.07	3	14
A1310.050.07	5	14
A1310.070.07	7	14
A1310.090.07	9	14



Joint sectionnables

Matière : NBR
Convient pour raccords AB107 - AB263 (voir pages 1.48 + 1.52)

Températures d'utilisation : -20 à +100°C

Référence article	 G	Ø mm	H mm
AB 107.00.03	M12/Pg7	4,0 - 7,0	5,0
AB 109.00.03	M16/Pg9	5,0 - 10,0	5,5
AB 111.00.03	Pg11	8,0 - 12,0	6,0
AB 113.00.03	Pg13	8,0 - 12,0	6,0
AB 116.00.03	M20/Pg16	8,0 - 15,0	7,0
AB 121.00.03	M25/Pg21	10,0 - 19,0	8,0
AB 129.00.03	M32/Pg29	18,0 - 27,0	9,5
AB 136.00.03	M40/Pg36	24,0 - 33,0	12,0
AB 142.00.03	M50/Pg42	30,0 - 39,0	14,0
AB 148.00.03	M63/Pg48	36,0 - 45,0	14,0

