Alle Rechte vorbehalten/ *All rights reserved*



Wire	Tinned copper
Gauge	AWG 28/7 0,089 mm²
Voltage rating	300 Vr.m.s
Current rating	1,3 A at 10°C rise above ambient
Capacity unbalanced	45,9 pF/m at 1 MHz
Impedance unbalanced	105 Ω
Propagation delay	4,9 ns/m nominal
Insulation material	PVC
Temperature rating	-20°C (operating) / -30°C (static) to +105°C
Flammability rating	Flame retardant VW1
Insulation resistance	100 MΩ/km
Approval	UL AWM style 2651

Part number	Length per reel	Color
09 18 026 7004	100 m (328 feet)	Grey
09 18 026 7001 001	30,48 m (100 feet)	Black
09 18 026 7001	30,48 m (100 feet)	Grey

Mod.	Dat.	Name
EC01360	19/02/10	SC
34400	17/09/07	PK
33788	24/07/06	PK
33246	20/10/05	JMDR

	Dat.	Name
Detail.	20/10/05	JMDR
Insp.		
Stand.		

All Dim. in mm
Orig. Size DIN A 4

HARTING EURL
F-95972 Paris

SEK 18 flat cable
26 poles

Maßstab/ *Scale* 10:1

TB 09 18 026 700X

Sub.

Blatt/ *Page* 1/1