


HONEYWELL PART NUMBER
V15T16-CZ300A06-K
PRODUCT CODE
CFW2059



CHARACTERISTICS		ELECTRICAL DATA		DESIGN UNITS: MM		DRAWN	KSR	01APR08	Honeywell							
CONTACT ARRANGEMENT S.P.D.T		17 cec 16(4)A 250V~ 25T125 μ 5E4 RU c RU 16A 1/2HP 125/250VAC		TOLERANCES UNLESS NOTED:		CHECK	RJ	01APR08						TITLE SWITCH - BASIC		
OPERATING FORCE: 180gf MAX. DIFFERENTIAL FORCE: _____ RELEASE FORCE: 30gf MIN. FREE POSITION: _____ OPERATING POSITION: 20.6±1.6MM. PRE-TRAVEL: 3.2MM MAX. DIFFERENTIAL TRAVEL: 1.2MM MAX. OVER-TRAVEL: 1.3MM MIN. FULL OVERTRAVEL FORCE: _____				NO PLACE X ± ± ONE PLACE .X ± ± TWO PLACE .XX ± ± 0.40 THREE PLACE .XXX ± ± ANGLES X ± ± 2°		THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.		INTERPRET PER ASME Y14.5M-1994 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY		SIZE B	TYPE I	CAGE CODE	DRAWING NAME V15T16-CZ300A06-K			
				THIRD ANGLE PROJECTION 				AutoCAD		SCALE	NTS			SHEET	1	OF 1