

**DA15S064T -**  
**D-Subminiature : Cable**  
**Connector 15 Way Socket**  
**Solder Bucket, without**  
**Accessory**



OBSOLETE


[www.fci.com](http://www.fci.com)

### Alternate Products

DA15S064TLF

### Specifications

<b>General</b>	
<b>Contact type</b>	Signal
<b>Gender</b>	Socket
<b>Number of contacts (Total)</b>	15
<b>Orientation</b>	Straight
<b>Product Type</b>	Connector
<b>Termination Style</b>	Solder Bucket
<b>Dimensional</b>	
<b>Size (Shell)</b>	A
<b>Size (Wire)</b>	20 AWG max. on Signal
<b>Electrical</b>	
<b>Current rating</b>	5A per Signal Contact
<b>Resistance (Contact)</b>	< 10 milli ohms
<b>Voltage rating</b>	300V rms at 50 Hz
<b>Voltage rating (DWV - Dielectric withstanding)</b>	1000V rms
<b>Mechanical</b>	
<b>Durability (Mating cycles)</b>	> 200 Cycles
<b>Durability (Plating - Mating cycles)</b>	Std Class (</=200 Mating Cycles)
<b>Extraction force (Mating part)</b>	0.3N min. per Contact
<b>Extraction force (Signal)</b>	0.3N min. per Contact
<b>Insertion force (Mating part)</b>	5N max. per Contact
<b>Insertion force (Signal)</b>	5N max. per Contact
<b>Mounting</b>	
<b>Attachment</b>	Cable
<b>Mounting accessory</b>	without Accessory
<b>Mounting options</b>	without Accessory
<b>Physical</b>	
<b>Plating (Contact)</b>	Gold over Nickel
<b>Plating (Shell)</b>	Semi Bright Nickel
<b>Plating (Solder tail)</b>	SnPb
<b>Plating (Termination)</b>	Tin-Lead over Nickel
<b>Temperature (Range)</b>	-55°C to +125°C
<b>Approvals / Certifications</b>	
<b>Approvals / Certifications</b>	Recognized (File E 118235)
<b>Other Features</b>	

**Most Popular Configuration**

Not Applicable