

TECHNICAL DATA
1/2

CRC DRY LUBE F
Grease and oil free lubricant
Ref. : 10257



1. GENERAL DESCRIPTION

Grease and oil free lubricant for the lubrication of wooden, plastic or metal surfaces. Clean, and not sticky dry film PTFE lubricant. Resistant till 250°C.

2. FEATURES

- Particularly suitable for use in areas where a wet film lubricant cannot be used due to possible environmental dust and dirt adherence.
- Clean, dry and non-oily.
- Functional over a wide temperature range.
- Produces very low coefficient of friction.
- High temperature resistance.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- NSF registration :H1 (registration number: 141273).

3. APPLICATIONS

- Plastic drives and sliding mechanisms.
- Fine mechanics.
- Pneumatic tools.
- Precision instruments.
- Valves.
- Surface lubrication.
- Particularly suitable in low load, low speed applications.

4. DIRECTIONS

- Shake well before use.
- Shake until the agitator ball moves freely in the can.
- To remove residues or excess of product, make use of one of the CRC cleaners.
- Spray from a distance of approximately 20 - 30 cm.
- Dry at room temperature.
- Do not use on energized equipment.
- To remove residues or excess of product, make use of one of the CRC cleaners.


A safety data sheet (MSDS) according to EC Regulation N°1907/2006 Art.31 and amendments is available for all CRC products.

Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives.



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com





TECHNICAL DATA
2/2

CRC DRY LUBE F
Grease and oil free lubricant

Ref. : 10257

5. TYPICAL PRODUCT DATA (without propellant)

Appearance	: propane/butane propelled liquid
Color	: white
Odor	: Characteristic odor
Density	: 0.73 g/cm ³ (@ 20°C)
Operating temperature active product	: -150 to +260 °C
Solubility	: Insoluble in water

6. PACKAGING

aerosol : 12 x 400 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10257 03 1208 03
Date : 10 February 2011



Manufactured by :
CRC Industries Europe BVBA
Touwslagerstraat 1 – 9240 Zele – Belgium
Tel (32) (0) 52/45.60.11 Fax (32) (0) 52/45.00.34
www.crcind.com

