

Contenu du Kit

95 pièces par valeurs

Valeur	Tolérance	Tension	Diélectrique
0,47 pF	0,25 pF	50V	NPO
0,68 pF	0,25 pF	50V	NPO
1 pF	0,25 pF	50V	NPO
1,5 pF	0,25 pF	50V	NPO
2,2 pF	0,25 pF	50V	NPO
3,3 pF	0,25 pF	50V	NPO
4,7 pF	0,25 pF	50V	NPO
6,8 pF	0,50 pF	50V	NPO
10 pF	0,05	50V	NPO
15 pF	0,05	50V	NPO
22 pF	0,05	50V	NPO
33 pF	0,05	50V	NPO
47 pF	0,05	50V	NPO
68 pF	0,05	50V	NPO
100pF	±5%	50V	NPO
150pF	±5%	50V	NPO
220pF	±5%	50V	NPO
100 pF	±10%	50V	X7R
150 pF	±10%	50V	X7R
220 pF	±10%	50V	X7R
330 pF	±10%	50V	X7R
470 pF	±10%	50V	X7R
680 pF	±10%	50V	X7R
1 nF	±10%	50V	X7R
1,5 nF	±10%	50V	X7R
2,2 nF	±10%	50V	X7R
3,3 nF	±10%	50V	X7R
4,7 nF	±10%	25V	X7R
6,8 nF	±10%	16V	X7R
10 nF	±10%	16V	X7R
15 nF	±10%	16V	X7R
22 nF	±10%	16V	X7R
10 nF	± 20 %	16V	Y5V
22 nF	± 20 %	16V	Y5V
47 nF	± 20 %	16V	Y5V
100 nF	± 20 %	16V	Y5V