

Contenu du KIT

48 pièces par valeurs

Valeur	Tolérance	Tension	Diélectrique		Valeur	Tolérance	Tension	Diélectrique
0,47 pF	±0,25 pF	50V	NPO		100 pF	±10%	50V	X7R
0,68 pF	±0,25 pF	50V	NPO		150 pF	±10%	50V	X7R
1 pF	±0,25 pF	50V	NPO		220 pF	±10%	50V	X7R
1,5 pF	±0,25 pF	50V	NPO		330 pF	±10%	50V	X7R
2,2 pF	±0,25 pF	50V	NPO		470 pF	±10%	50V	X7R
3,3 pF	±0,25 pF	50V	NPO		680 pF	±10%	50V	X7R
4,7 pF	±0,25 pF	50V	NPO		1 nF	±10%	50V	X7R
6,8 pF	0,50 pF	50V	NPO		1,5 nF	±10%	50V	X7R
10 pF	±5%	50V	NPO		2,2 nF	±10%	50V	X7R
15 pF	±5%	50V	NPO		3,3 nF	±10%	50V	X7R
22 pF	±5%	50V	NPO		4,7 nF	±10%	50V	X7R
33 pF	±5%	50V	NPO		6,8 nF	±10%	50V	X7R
47 pF	±5%	50V	NPO		10 nF	±10%	50V	X7R
68 pF	±5%	50V	NPO					
100pF	±5%	50V	NPO		15 nF	±10%	25V	X7R
150pF	±5%	50V	NPO		22 nF	±10%	25V	X7R
220pF	±5%	50V	NPO					
330pF	±5%	50V	NPO		33 nF	±10%	16V	X7R
470pF	±5%	50V	NPO		47 nF	±10%	16V	X7R
680pF	±5%	50V	NPO		68 nF	±10%	16V	X7R
					100 nF	±10%	16V	X7R
1nF	±5%	50V	NPO					
1,5nF	±5%	50V	NPO		10 nF	± 20 %	50V	Y5V
					22 nF	± 20 %	50V	Y5V
					47 nF	± 20 %	50V	Y5V
					100 nF	± 20 %	50V	Y5V
					220 nF	± 20 %	16V	Y5V
					470 nF	± 20 %	16V	Y5V