




HARTMANN

Dual Push Button Switches

PICO-D 307 AK - 2



■ contacts with abrasion resistant hard gold plating

■ 100% electronic final inspection and testing

Gold-gold-contacts have low and stable contact resistance. ISO 9001:2000 approved production together with 100% electronic final inspection and testing guarantee reliable operation. Many special designs are available on request or can be built according to customer's specification.

Electrical Data

Operating voltage	40 V
Contact load, dynamic (resistive)	100 mA
Contact load, static	0,5 A
Contact resistance for PCB AK	< 100 m
(measured from supply line to output)	

Mechanical Data

Width	7,62 mm
Perm. ambient temp	-20 ... +60 °C
Max. mech. lifetime	100 000 Schaltschritte
Operating force 10-digit	ca. 3 N
Operating force 16-digit	ca. 5 N
Weight	ca. 2 g
Digit height 10-digit	3,1 mm
Digit height 16-digit	2,4 mm
Click action	fühlbar
Vibration testing	nach DIN EN 60068-2-6
Shock testing	nach DIN EN 60068-2-27


Material

Housing	PPO
PCB base material	FR4 bzw. CEM3 DIN IEC249-2
Contact surface	Au über Ni auf Cu
Sliding contact	Au über Ni auf CuSn6

Configuration

Codes	Hexadecimal Complement , 16 Positions
-------	---------------------------------------

PCB



Short

Suffix	without solder pins
--------	---------------------

Colour	housing black, drum black, digits white
--------	---