

AK1700/..-3.5-GREEN



Technical Data

Wire sizes		Insulating Material	
Solid min	0.14 mm²	Material	PA 6.6
Solid max	1.5 mm²	Flammability Class	UL 94 V-0
Stranded (flexible) min	0.14mm²	Temperatures	
Stranded (flexible) max	1.5 mm²	Operating Temperature	-30 °C - 105 °C
Stranded with Ferrule min	0.25 mm²	Store Temperature	-40 °C - 105 °C
Stranded with Ferrule max	1.0 mm²	Wave Soldering Process	
Dimensions		Soldering Temperature, recommended	-
Stripped Length	7.0 mm	Peak Soldering Time, recommended	-
Materials		Reflow Process	
Clamp	Brass	Soldering Temperature, recommended	-
Screw	Bronze	Peak Soldering Time, recommended	-
Contact Spring	Bronze		


Colours

	GREEN, RAL 6018
	LIGHT GREY, RAL 7035
	LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions. Special colours on request.

Counterparts (Spacing 3.5 mm)

Pin Strip
STL1550
In combination of connectors with different admission data, the lower value is valid.



Order Data (Spacing 3.5 mm)

Poles	Width (mm)	Article Designation	Article Number	PU
2	7.00	AK1700/2-3.5-GREEN	51700020001 F	200
3	10.50	AK1700/3-3.5-GREEN	51700030001 F	200
4	14.00	AK1700/4-3.5-GREEN	51700040001 F	200
5	17.50	AK1700/5-3.5-GREEN	51700050001 F	200
6	21.00	AK1700/6-3.5-GREEN	51700060001 E	100
7	24.50	AK1700/7-3.5-GREEN	51700070001 E	100
8	28.00	AK1700/8-3.5-GREEN	51700080001 D	50
9	31.50	AK1700/9-3.5-GREEN	51700090001 D	50
10	35.00	AK1700/10-3.5-GREEN	51700100001 D	50
11	38.50	AK1700/11-3.5-GREEN	51700110001 D	50
12	42.00	AK1700/12-3.5-GREEN	51700120001 D	50
13	45.50	AK1700/13-3.5-GREEN	51700130001 D	50
14	49.00	AK1700/14-3.5-GREEN	51700140001 D	50
15	52.50	AK1700/15-3.5-GREEN	51700150001 D	50
16	56.00	AK1700/16-3.5-GREEN	51700160001 D	50
17	59.50	AK1700/17-3.5-GREEN	51700170001 D	50
18	63.00	AK1700/18-3.5-GREEN	51700180001 D	50
19	66.50	AK1700/19-3.5-GREEN	51700190001 D	50
20	70.00	AK1700/20-3.5-GREEN	51700200001 D	50

Accessoires

Figure	Designation	Article Number
	Bridge, 2-pole, BR/2-3.5/3.81-L7.5	Art.-Nr. 50000000015
	Bridge, 3-pole, BR/3-3.5/3.81-L7.5	Art.-Nr. 50000000016
	Bridge, 2-pole, angled, BR/2-3.5/3.81-H-L7.5	Art.-Nr. 50000000029
	Bridge, 2-pole, insulated, BRI/2-7.0/7.62-L7.5-LIGHT GREY	Art.-Nr. 50000000018
	Series AK(Z)1700 with pull relief	Art.-Nr. on request

See pages 282 ff for detail and general accessories and see pages 12/13 concerning services.

Ratings

UseGroup	B	C	D		
Rated Voltage	300 V	-	300 V	160 V	
Rated Current	8 A	-	8 A	8 A	
Overvoltage Category				III	
Rated Wire Size				min	max
- solid	AWG 28-16	-	AWG 28-16	0.5 mm² (6 A)	1.5 mm² (8 A)
-stranded	AWG 28-16	-	AWG 28-16	0.5 mm² (6 A)	1.5 mm² (8 A)
Torque	0.25 Nm	-	0.25 Nm	0.25 Nm	
Screw Size	M2	-	M2	M2	
Test Voltage	1.60 kV	-	1.60 kV	2.5 kV	
Pollution Degree				3	