



SAFETY PATCH CORDS

According to IEC 1010.
Basic or supplementary insulation.
Surge overvoltage category II.
Pollution degree 2.
1000V CAT II

BDSA/BDSA PATCH CORDS

Plug / plug stackable safety patch cords.
☞ *packaging : 10*

Max current :
1mm² cross section wire : 15A
2mm² cross section wire : 30A



R 948 3xx 6xx

0 : 25 cm (10")
1 : 50 cm (20")
2 : 100 cm (40")
3 : 150 cm (60")
4 : 200 cm (80")

0 : Black
1 : Red
2 : Green
3 : Blue
4 : Yellow

00 : 1mm² PVC 3.5 (1.4") dia.
02 : 2mm² PVC 3.5 (1.4") dia.

BMS/BMS PATCH CORDS

Plug / plug non stackable safety patch cords.

☞ *packaging : 10*

Max current :
1 mm² cross section wire : 15A
2 mm² cross section wire : 30A



R 948 0xx 6xx

2 : 25 cm (10")
4 : 50 cm (20")
5 : 100 cm (40")
6 : 150 cm (60")
7 : 200 cm (80")

0 : Black
1 : Red
2 : Green
3 : Blue
4 : Yellow

00 : 1mm² PVC 3.5 (1.4") dia.
02 : 2mm² PVC 3.5 (1.4") dia.

PTS/BMS CORDS

One red and one black non stackable plug / test probe
Safety patch cord.

1mm² and 100cm (40") long PVC wire.

☞ *packaging : 10 pairs*



R 948 959 600